

# Data sheet

## Coupling plug (NW10) R 3/4"(male thread), Steel hardened & nickel plated

**Item number:**

KSG 34 NW10



Example illustration

### Item description

**Materials:**

Type nickel-plated brass: Body: nickel-plated brass, sliding sleeve: nickel-plated steel, seal: NBR

Type brass/steel: Body: nickel-plated brass/steel (QPQ), sliding sleeve: nickel-plated brass, seal: NBR

Type stainless steel: Body and sliding sleeve: 1.4305, seal: FKM

**Temperature range:**

-20°C to max. +100°C (Stainless steel: -15°C to max. +200°C)

**Operating pressure:**

-0,95 to 35 bar

**Compatible with\*\*:**

Rectus (27, 41, 1700, 1727), TEMA (1700), CEJN (410)

**Flow\*\*\*:**

Nickel-plated brass/M 1.4305: 2150 l/min (option: **-BA**: 1020 l/min), brass/steel: 3600 l/min

**Note:**

Coupling plugs with valve for double-sided shut off (**-BA**) can only be used with the special coupling sockets (**-BA**) provided for them.

**Optional:**

Body made from 1.4404 **-ES4A**, with valve for double-sided shut-off **-BA**

### Properties

<b>Material</b>	Steel hardened & nickel plated
<b>Thread external</b>	R 3/4"
<b>shut-off on both sides</b>	no

<b>Temperature range [°C]</b>	-20 to +200
-------------------------------	-------------

**Further information:**

<b>Weight</b>	80 g / pcs
<b>GTIN</b>	4050571449117
<b>Customs duty number</b>	84812090
<b>RoHS compliant</b>	Yes