



STXVNR

mit Sechskant
Non-return valve, with hexagon
Valvola di non ritorno F.F.



Code	G	H	L		NI/min*
STXVNR-M5	M5	5,5	26,5	8	190
STXVNR-1/8	G1/8	8,5	36,5	13	920
STXVNR-1/4	G1/4	9	42,5	16	1600
STXVNR-3/8	G3/8	12	51	20	2430
STXVNR-1/2	G1/2	14	62	24	3500

* Ermittlung der Durchflusswerte bei 6 bar * Evaluation of flow rate at 6 bar
* portata nominale a 6 bar

Körper:	CW614N vernickelt
Body:	CW614N nickel-plated
Corpo:	ottone CW 614N nichelato
O-Ring:	NBR
O-Ring:	NBR
O-Ring:	NBR 70 SH
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-10°C bis +70°C
Working temperature:	-10°C up to +70°C
Temperatura di utilizzo:	da -10°C a +70°C
Betriebsdruck:	max. 10 bar
Working pressure:	max. 10 bar
Pressione di utilizzo:	max. 10 bar
für geölte und ungeölte Druckluft	
for lubricated and non-lubricated compressed air	
per aria compressa sia lubrificata che non	