


Mini-Kugelhahn

konisch

Mini ball valve con.

Valvola a sfera micro maschio conico femmina cilindrica



Code	R	G	H	L	D	E	DN	sw1	sw2
VS110-3/8	R3/8	G3/8	11,5	44,5	19,5	23	8	18	-

Betriebstemperatur:	-20 °C bis +80 °C
Operating temperature:	-20 °C to +80 °C
Temperatura di esercizio:	da -20 °C a +80 °C
Betriebsdruck:	20 bar
Inlet pressure:	20 bar
Pressione di esercizio:	20 bar
Körper/Kugel:	Messing verchromt
Body/ball:	brass chrome-plated
Corpo/sfera:	ottone cromato
Griff:	PA66
Handle:	PA66
Leva:	PA66
O-Ring:	NBR 70
O-ring:	NBR 70
O-Ring:	NBR 70
Gewinde:	DIN EN ISO 228/ DIN EN ISO 10226
Thread:	DIN EN ISO 228/ DIN EN ISO 10226
Filettatura:	DIN EN ISO 228/ DIN EN ISO 10226
Einsatzgebiete:	Luft-, Wasser-, Ölkreisläufe, Einsatz auch im mittleren bis niedrigen Vakuum möglich.
Applications:	Air, Water and Oil dynamics circuits, use also in medium to low vacuum.
Campo di applicazione:	Aria, acqua e circuiti oleodinamici; e' possibile l'utilizzo per medio/ basso vuoto pneumatico.